

Type	Model	Dimension		Voltage (V)	Power (W)	PFC	CCT(K)	CRI	Illuminance(LUX)		Luminous Efficacy (lm/W)
		Length (mm)	Diameter (mm)						1m	2m	
60 cm	DSL10T6009G01	601.5	30	AC85~265	9	>0.45	6000~6800	>70	145±30	45±10	65±10
	DSL10T6009G01-01						2600~3400	>55	125±30	35±10	55±10
	DSL10T6009G01-02	594.5					6000~6800	>70	145±30	45±10	65±10
	DSL10T6009G01-03						2600~3400	>55	125±30	35±10	55±10
	DSL10T6009G02	601.5		AC85~277		=0.9	6000~6800	>70	145±30	45±10	65±10
	DSL10T6009G02-01						2600~3400	>55	125±30	35±10	55±10
	DSL10T6009G02-02	594.5					6000~6800	>70	145±30	45±10	65±10
	DSL10T6009G02-03						2600~3400	>55	125±30	35±10	55±10
120 cm	DSL10H2018G01	1212.5	AC85~265	18	>0.45	6000~6800	>70	250±30	80±15	65±10	
	DSL10H2018G01-01					2600~3400	>55	230±30	70±15	55±10	
	DSL10H2018G02		AC85~277		=0.9	6000~6800	>70	250±30	80±15	65±10	
	DSL10H2018G02-01					2600~3400	>55	230±30	70±15	55±10	
150 cm	DSL10H5022G01	1514.5	AC85~277	22	=0.9	6000~6800	>70	285±45	95±15	65±10	
	DSL10H5022G01-01					2600~3400	>55	240±45	80±15	55±10	